



TECHNICAL SPECIFICATIONS

U	HDPE (High Density Polyethylene)
#	Black or White (on Request)
8)	46.5" x 23.6" x 1.2" (1180mm x 600mm x 30mm)
8 ‡	8.8lbs/m ² (4 kg/m ²)
# 'o	Square
#)	2.55" x 1.18" x 0.13" (65mm x 30mm x 3.2mm)
# ‡ u	0.13" (3.2mm)
# 'k	> 30 700 lbs/sq.ft. (150 tons/m ²)
O "' #	> 65 100 lbs/sq.ft. (Over 350 tons/m ²)
u 'k	-52°C to- +90°C
# 'k	Excellent
y † k	Excellent
o "' o	0.2" -0.6" (5-15mm)

CERTIFICATES/COMPLIANT

DIN 14090 Approved (Fire Service Access)
 Q-) Used in SUDS and LEED compliant porous paving BMPs for ideal draining and minimal environmental impact.
 *) * # Used in ADA disability compliant surfaces for pedestrians, bicycles, & wheelchair traffic.
 - ** Maryland Department of the Environment, Montgomery County, and City of Victoria, British Columbia.

SUITABLE FOR

Residential parking, Commercial Parking, RV parking/Access Lanes, Public Pedestrian Applications, Bicycle Trails, and Fire Service Access

Install Video
[youtube.com/watch?v=XYRECpcRIuM](https://www.youtube.com/watch?v=XYRECpcRIuM)

